

24 Series Fisheye Remover

24 Series Fisheye Remover is an additive specially formulated to help avoid and prevent fish-eyes. Fisheye Remover can be used with virtually all types of urethane and non-urethane 2K topcoats. Use for a smooth finish over surfaces that show evidence of fish eyeing usually due to contamination.



SURFACE PREPARATION

Refer to topcoat manufacture for surface preparation.

MIXING & APPLICATION

Mix with HB777 euro Clear-coats and HB Series 2K Clear-coats
Use 1/4 to 1/2 ounce per sprayable quart.

DESCRIPTION

Fish-Eye Eliminator is designed for use when uncontrolled oil or silicone contamination occurs. It overcomes contamination so the coating will lay flat and smooth, removing any imperfections in the surface.

COMPONENTS/MIXING RATIO

To one (1) quart of ready-to-spray 2K Urethane color or clear, add up to ¼ ounce of Fish Eye Eliminator. Use sparingly. **Do not use in primers or Base-Coat.**

- POT LIFE AT 77° F : N/A
- CLEAN UP: Use a High Quality Lacquer thinner or zero VOC solvents. (Check local regulations)
- PHYSICAL DATA: See SDS

APPLICATION

Note : Use the proper application instructions for the system you are using this additive in. Do not delay application and clean up immediately.

SAFETY

Refer to Safety Data Sheet (SDS) for complete safety instructions. The technical data sheet listed has been compiled in good faith for your convenience and guidance. No warranty, expressed or implied, is intended or given by the information on this sheet.



Scan QR-code Visit www.hydrabond.com to assure you are using most updated TDS, to view in other languages and for links to Standard Operating Procedures (SOPs).