

SDS SAFETY DATA SHEET

SECTION 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name: 4EVER loor coating FOP (Base component) Yellow (Part A)

Product codes : **HB606, HB609, HB612** (SDS NO): Eb46_128-1

· Details of the supplier of the safety data sheet

MANUFACTURED FOR:

BHG Import Exports Inc.
715 N Central Ave. Suite 213
Glendale CA 91203 United States

· Information department: Product safety department
· Emergency telephone number:
24 Hrs Emergency Contact:
CHEMTREC 628320
FOR USA AND CANADA: 1-800 424- 9300
OUTSIDE USA AND CANADA: +1 703 -527- 3887

SECTION 2: HAZARDS IDENTIFICATION

PHYSICAL , CHEMICAL HAZARDS	Flammable liquid	2
HEALTH HAZARDS :	Acute toxicity(Inhalation : Oral)	5
	Acute toxicity(Inhalation : Mist)	3
	Acute toxicity(Inhalation : Skin)	5
	Skin corrosive nature and stimulative	2
	Damage to the eye	2A
	Reproductive toxicity	1B
	Carcinogenicity	2
	Speciic target internal organs and systemic toxicity	
	(Central nerve system)	2
	(Anesthetic action)	3
	(Anesthetic action)	3
	(Orbital stimulativeness)	3
	Speciic mark organ and the whole body toxicity	
	(repetition disclosure)	
	(Respiratory organ and nerve system)	1
	Suction, the respiratory organ harmful efect	1
	Aquatic environment acute harmful efect	1
	Aquatic environment chronic harmful efect	2
	Suction respiratory-organs hazardous property	2

LABEL ELEMENTS :



- HAZARDOUS INFORMATION :
- Danger
 - Flammable liquid , vapor
 - Harmful for inhalation
 - Irritation to the eye
 - Generative toxicity
 - Harmful for Central nervous system, Respiratory organs, Anesthetic action for repetition of use

- PRECAUTIONS :
- Read cautions thoroughly before use.
 - Avoid smoking.
 - Keep away from heat , sparks and flame.
 - Use only with adequate ventilation.
 - Avoid breathing vapor.
 - Avoid contact with eyes, skin and clothing.
 - Keep container closed.
 - Wash thoroughly after handling.
 - Use adequate fire fighting measures.

- FIRST AID :
- If inhaled, remove to fresh air . If not breathing , give artificial respiration. If breathing is difficult, give oxygen.
 - If swallowed, do not induce vomiting.
 - In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 - Wash clothing before reuse.
 - In all cases get medical attention immediately.

SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENT	CAS NO.	CONCENTRATION (Wt. %)
Epoxy Resin	25068-38-	50 ~ 60
Pigment	-	40 ~ 50
Titanium Dioxide	13463-67 -	1 ~ 10
Xylene	1330-20-7	1 ~ 5
Ethylbenzene	100-41-4	1 ~ 5

SECTION 4: FIRST AID MEASURES

- SKIN CONTACT : Remove contaminated clothing and foot wear. Wash skin thoroughly with plenty of clean, fresh water and soap or proper skin cleaner. DO NOT use thinners and solvents. Wash clothing before reuse.
- EYE CONTACT : Flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, get medical attention
- INHALATION : Remove to fresh air, keep the patient warm and at rest. Administer artificial respiration if breathing is irregular or has stopped. Get medical attention.
- INGESTION : DO NOT induce vomiting. Keep at rest. Get medical attention immediately.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISH MEDIA CO₂, alcohol resistant foam, dry chemical, powder spray, sand
 INSTRUCTIONS : Cool exposed containers with water spray. Never direct water in the container in order to prevent any splashing of the product. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SMALL SPILL : Remove all sources of ignition and ventilate the area. Absorb with an inert material such as sand, earth, vermiculite, diatomaceous earth and place in an appropriate waste disposal container.
 LARGE SPILL : Stop leaking if without risk. Eliminate all sources of ignition. Contain with an inert material recover as much as possible and place the remainder in an appropriate waste disposal container. Warn unauthorized personnel to evacuate. Prevent entry into drains and sewers or confined areas. If the product enters drains and sewers contact the local water company immediately. In case of contamination of streams, rivers or lakes, contact local, regional or national authority.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS : Use only in well ventilated areas. Avoid inhalation and contact with eyes, skin and clothing. Wear appropriate personal protective equipment. Ground and bond all containers when transferring the material. Empty containers may retain product and product vapor. DO NOT expose to heat, open flame, sparks, direct sunlight or other ignition sources such as cutting, welding, drilling, grinding or static electricity. DO NOT pressurize. Provide adequate safety showers and eyewashes in the area of use. Keep out of reach of children.
 STORAGE : Keep away from heat. Keep away from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. Ground all equipment containing material. Smoking, eating and drinking should be prohibited in areas of storage and use. Keep out of reach of children.

SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

EXPOSURE LIMITS :	Xylen TLV TWA: 100(ppm) from ACGIH Ethylbenzene TLV TWA: 100(ppm) from ACGIH
ENGINEERING CONTROLS :	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Provide adequate safety showers and eyewashes in the area of use.
PERSONAL PROTECTION :	Personal Protective Equipment may vary depending on the job being performed.
EYE/FACE :	Wear eye protection such as safety glasses with side shields, splash goggles or face shield with safety glasses.
SKIN :	Avoid skin contact. Impervious gloves should be worn. Other items may include long sleeves, lab coats, or impervious jackets.
RESPIRATORY :	Determine if airborne concentrations are below the recommended exposure limits in accordance your company's PPE program and regulatory requirements. If they are not, select NIOSH approved respirators are generally adequate protection from the concentration levels encountered. Air-purifying respirators are generally adequate for organic vapors. Use positive pressure, supplied air respirators if there is potential for an uncontrolled release. If exposure levels are unknown, or under circumstances where air-purifying respirators may not provide adequate protection.

SECTION 9: TOXICOLOGICAL INFORMATION

PHYSICAL STATE :	Liquid
ODOR :	Mild, rather pleasant, like wine
BOILING POINT :	114°C ~ 140°C
VAPOR PRESSURE :	133Pa(20°C)
FLASH POINT :	26.7°C
AUTO IGNITION POINT :	No Data
SPECIFIC GRAVITY :	1.27 ~ 1.52(Water =1)
SOLUBILITY :	Soluble in solvent
VOC :	140g/L

SECTION 10: STABILITY AND REACTIVITY

STABILITY :	Stable under ordinary conditions of use and storage
CONDITIONS OF INSTABILITY :	Heat
HAZARDOUS DECOMPOSITION PRODUCTS :	Carbon Monoxide , Formaldehyde
HAZARDOUS POLYMERIZATION :	Will not occur.
INCOMPATIBILITY :	Heat, lame, strong oxidizers, nitric and sulfuric acids, chlorine, nitrogen tetraoxide.

SECTION 11: STABILITY AND REACTIVITY

PRIMARY ROUTES OF ENTRY : Skin contact, eye contact, inhalation, and ingestion.

TOXICITY TO ANIMALS :
 Xylene
 LD50: 400mg/kg (Rat)
 LC 50 : 3000ppm(Rat)
 Ethylbenzene
 LD50 : 3500mg/kg (Rat)
 Titanium Dioxide
 LD50: 2400mg/kg (Rat)
 LC 50 : 6820mg/m3(Rat)

SPECIAL REMARKS ON TOXICITY TO ANIMALS :
 Investigated as a mutagen and reproductive efector.

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE : When released to the atmosphere, it will photo degrade in hours (polluted urban atmosphere) to an estimated range of 4 to 6 days in less polluted areas. Rain-out should be signiicant

ECO-TOXICITY : Insoluble in water

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL : Dispose of product in an appropriate and approved waste disposal facility in accordance with applicable national, prefectural and local regulations.

SECTION 14: TRANSPORT INFORMATION

* **Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations); **USA DOT** 49 cfr 173.173 b(2) and Consumer Commodity (49 cfr 173.150(c), Regulations.

Sizes 5 L and under

Limited Quantity



Sizes greater than 5 L

UN number: UN1263
Shipping Name: PAINT
Class: 3
Packing Group: III
ERG Guide NO.: 128



Transport in bulk according to Annex II of MARPOL73/78 and IBC Code

Noxious Liquid ; Cat. Y

Ethylbenzene; Xylene (Mixture of isomers); Toluene

Limitations and Exceptions

Quantity Limitations	On passenger aircraft/rail: 5L On cargo aircraft only : 60L
Remarks	ORM-D 49 CFR 173.150,156,306
ADR	
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging : 30ml Maximum net quantity per outer packaging : 500ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging : 30ml Maximum net quantity per outer packaging : 500ml

SECTION 15: OTHER REGULATORY INFORMATION

OTHER REGULATIONS :	This section does not reference all applicable regulatory compliance lists.		
FIRE MANAGEMENT LAW :	Category 4 Petroleum Group 2 (Water insolubility) Hazardous Category III		
INDUSTRIAL SAFETY AND HEALTH LAW :	Toxic substance which should be noticed		
REGULATION OF ORGANIC SOLVENTS INTOXICATION PREVENTION :	Category 2		
PRTR LAW :	Xylene	5%	Category I 53
	Ethylbenzene	5%	Category I 85

SECTION 16: OTHER INFORMATION

REFERENCE :	Material Substance Database/ Japan Paint Industrial Association Pocket Book for Solvents Reference of Hazardous and Toxic Chemical Substance/ Japan Industrial Safety and Health Association (JISHA)
LEGAL DISCLAIMER:	MSDS of other manufacturers

BHG IMPORT EXPORT INC. cannot guarantee the accuracy, adequacy or completeness of information in this Material Safety Data Sheet, because it has been compiled from our experience, knowledge and various publications believed to be reliable. It is the customer's responsibility for ensuring that the product is used, handled, stored, and disposed in accordance with the safety precautions herein and in compliance with applicable national, prefectural, or provincial, and local laws.

BHG IMPORT EXPORT INC. disclaims liability for any loss, damage, or personal injury that arises from, or is in any way related to use of the information contained in this data sheet.