

24 Series Additives

24 Series Fisheye Remover

HB6346
HB6347
HB6582

Technical Data Sheet

24 Series Fisheye Remover is an additive specially formulated to help avoid and prevent fisheyes. Fisheye Remover can be used with virtually all types of urethane and non-urethane 2K topcoats. Use for a smooth finish over surfaces that show evidence of fish eyeing usually due to contamination.

SURFACE PREPARATION



Refer to topcoat manufacture for surface preparation.

MIXING & APPLICATION



Mix with HB777 euro Clearcoats and HB Series 2K Clearcoats or 2K Primers. Use 1/4 to 1/2 ounce per sprayable quart.

PRODUCT SPECIFICATIONS

Color: Clear liquid	Shelf Life: 1 year
Size: 8 Oz & 16 Oz Metal Can	Solids: 13.01% by weight

REGULATORY

	6737	Weight % of Exempt Compounds	0
VOC Actual	6.52#/gal (781 g/l)	Volume % of Exempt Compounds	0
VOC Regulatory	6.52#/gal (781 g/l)	Density of Material #/gal	7.50
Weight % of Volatiles	86.99		
Weight % of Water	0		

LIMITATIONS & PRECAUTIONS

For use only by professional, trained painters. Not for sale to or use by the general public. Before use, read and follow all TDS, label and SDS precautions.



Visit www.hydrabond.com to assure you are using most updated TDS, to view in other languages and for links to Standard Operating Procedures (SOPs).

Rev 03/18